



HYDRALASTIC

836

A superior cold-applied, single-component waterproofing membrane



HYDRALASTIC 836 keeps water where it belongs – whether it's applied inside, outside, horizontally or vertically! Designed with specifiers and end users in mind, this cold-applied, 98% solids, single-component membrane is ideal for positive side waterproofing for foundations and in between-slab applications.

HYDRALASTIC 836 is fast curing, low odor, solvent-free, resistant to early rainfall and able to withstand temperature extremes without cracking shrinking or slumping. Suitable for both above- and below-grade applications, **HYDRALASTIC 836** offers superior performance along with a variety of other benefits:

- Bonds to concrete, asphalt, wood, metal – may be applied to green concrete.
- Compatible with asphalt protection boards.
- Easy application translates to time and labor savings.
- Excellent elasticity and rebound characteristics.
- 98% high solids formulation means no shrinkage and increased coverage as compared to competitive products.
- No blisters due to solvent outgassing.
- No primer required.
- Extremely low odor.
- Will not harm EPS or styrofoam materials.
- Meets ASTM C 836.

For more information, samples or literature, visit www.wrmeadows.com or call 1-800-342-5976.



Scan on your smart phone to find out more.

follow us:

@wrmeadows

facebook.com/wrmeadows



W. R. MEADOWS®
SEALTIGHT®

QUALITY...INTEGRITY...
SERVICE...SINCE 1926