

GUARDIAN OF THE PAVEMENT



KOOL-ROD™

SMALLER SIZES FOR
SMALLER JOBS

It's In the BAG.

WE'VE BAGGED UP
BACKER ROD FOR
YOUR CONVENIENCE.



Search... Backer Rod in Bag



KOOL-ROD STANDARD BACKER ROD	
ROD DIAMETER	FEET PER BAG
1/2" (12.7 mm)	500' (152.4 m)
3/8" (9.5 mm)	230' (70.1 m)
1/4" (6.3 mm)	130' (39.6 m)
3/16" (4.8 mm)	75' (22.9 m)
1/8" (3.2 mm)	55' (16.7 m)

KOOL-ROD S SOFT-TYPE BACKER ROD	
ROD DIAMETER	FEET PER BAG
3/8" (9.5 mm)	230' (70.1 m)
1/2" (12.7 mm)	75' (22.9 m)
3/4" (19.0 mm)	30' (9.1 m)
1" (25.4 mm)	20' (6.1 m)

INSTALLATION:
 Use only on a prepared and compacted subgrade. Do not use on soft or wet subgrade. Do not use on a surface that is not clean, dry, and free of debris. Do not use on a surface that is not level. Do not use on a surface that is not prepared for backer rod application. Do not use on a surface that is not prepared for backer rod application. Do not use on a surface that is not prepared for backer rod application.

INSTALACION:
 La junta a aplicar debe ser sobre un subgrado preparado y compactado. No utilizar en subgrados blandos, húmedos o con agua. No utilizar en superficies que no estén limpias, secas y libres de suciedad. No utilizar en superficies que no estén preparadas para la aplicación de la junta. No utilizar en superficies que no estén preparadas para la aplicación de la junta. No utilizar en superficies que no estén preparadas para la aplicación de la junta.

W. R. MEADOWS, INC.
 309 S. Main Street, Springfield, IL 62760
 (618) 266-9976
 www.wrmeadows.com • info@wrmeadows.com

KOOL-ROD PRODUCTS

KOOL-ROD

DIAMETER	FEET/BAG
1/4" (6.35 mm)	500' (152.4 m)
3/8" (9.53 mm)	230' (70.1 m)
1/2" (12.7 mm)	130' (39.6 m)
5/8" (15.86 mm)	75' (22.86 m)
3/4" (19.05 mm)	55' (16.76 m)

COLOR: DARK GRAY

KOOL-ROD SOFT

DIAMETER	FEET/BAG
3/8" (10 mm)	230' (70.1 m)
5/8" (16 mm)	75' (22.9 m)
7/8" (22 mm)	35' (10.7 m)
1 1/8" (29 mm)	20' (6.1 m)

COLOR: GRAY

Get Yours Now! (847) 214-2100



DISTRIBUTED BY:

